

# AUSSI TRIM

## DATA SHEET

Aussi Trim is a ready to install, 3-in-1 insulated panel combining Trim (ribbed) Steel Roof, Polystyrene Insulation Core and Smooth Steel Ceiling. The state-of-the-art panels reduce radiant heat and come in a range of colours to suit your existing building. Engineered for Australia's tough environment with superior spanning (fewer beams) for sleek, designer finishes.



## SIZE SPECIFICATIONS


Panels Size (mm)	50	75	100	125	150
TRIM Overall Thickness (mm)	78	103	128	153	178
Panel Weight (kg/m <sup>2</sup> )	10.58	10.94	11.37	11.8	12.23
R Value 8oC m <sup>2</sup> KW	1.61	2.26	2.66	3.25	3.94
R Value 20oC m <sup>2</sup> KW	1.59	2.22	2.59	3.17	3.75

## GENERAL DATA

Width	1000mm (joined together)
Length	Cut to order (min 1.8m)
Min. Roof Pitch - TRIM	2° (35mm / meter)
Roof & Ceiling Profiles	Roof Trim (ribbed)   Ceiling Smooth (flat)
Roof Thickness and Material	0.42mm   AZ150 G550
Ceiling Thickness and Material	0.60mm   AZ150 G300
Max Skin Temperature	78° Dry Heat Sustained
Paint Finish and System	25% Gloss   AS/NZS 2728 and AS 1397
Core AS 1366: (Part 3 1992)	SL Grade Polystyrene 13.5 kg/m <sup>2</sup> - Fire-Retardant
"K" Value Core	0.037
Adhesive	Thermosetting two-part polyurethane CFC free

# AUSSI TRIM

## DATA SHEET



### EARLY FIRE HAZARD PROPERTIES

Ribbed Insulated Roofing–AS 1530.3–EPS-FR Panel

Index	Test Range	External Top Skin	Exposed Core
Ignitability	0-20	0	12
Spread of Flame	0-10	0	9
Heat Evolved	0-10	0	7
Smoke Developed	0-10	1	7

\*Tested by James Cook University to the latest “low high low” testing standard

**BUSHFIRE ATTACK LEVEL - BAL-40** (Bal-40 flashing available to cover exposed core)

### CUTBACKS

Roof profiles have a standard Right to Left (RH) cut back of 60mm. Also available in 80mm, 100mm, 120mm by request. Left to Right (LH) rebate available in 60mm only.



Aussi Panels are backed by a 15-year warranty against defects that may be caused by the manufacturing process. Refer to warranty for full details.

### GENERAL NOTES

\*Aussi Panels provides a materials estimate only and recommends the installer and/or certifier check the quote and final BOM for accuracy and suitability.

\*It is the responsibility of the Installer to check that the existing structure to which a patio or carport is being attached has sufficient strength for the additional loads. In some cases it may be advisable to engage a structural engineer to determine the suitability of the existing structure

\*Aussi Panels recommends non-trafficable signs be clearly displayed on or around any new insulated panel structure.

### MORE INFORMATION

Pemko Blue Pty Ltd t/a Aussi Panels

ABN 87 583 608 251 | A. 8 Andrew Campbell Dr, Narangba QLD 4504

P. 07) 3185 0295 | E. [sales@aussipanel.com.au](mailto:sales@aussipanel.com.au) | W. [aussipanel.com.au](http://aussipanel.com.au)