



2024 PRODUCT GUIDE

Aussie made for Aussie lifestyles



Contents

01	About Aussie Panels
02	Aussie Trim (Ribbed)
04	Aussie Corro
06	Roof Colours
08	Aussie Wall
10	Aussie Single Skin Roofing
12	Aussie Accessories
19	General Safety & Transport
21	Budget Patio Panels





About Aussie Panels

AUSSIE PANELS has been supplying insulated roofing and walls to South East Queensland for more than a decade.

We specialise in patio and carport kits plus provide materials for a wide range of projects including transportable buildings and cool rooms.

Our Aussie made Premium Colorbond range and Aussie Roof & Wall Panels Range are engineered and tested to meet Australian Standards.

We also supply Single-Skin roofing and even stock Cool Panels insulated roofing and walls at our Narangba warehouse.

It's a wide range of options backed by great service, friendly advice and competitive prices.



Aussie Trim (Ribbed)



AUSSIE TRIM (Ribbed Panel) delivers superior spanning capabilities compared to traditional roofing products.


The huge spans help create an architectural feel, while the smooth ceiling has no ugly rafters, adding style to your new entertainment and lifestyle area and value to your home.

Aussie Trim Fixing Guide

Panel Size	Metal Beam (Tek 14)	Timber Beam (Type 17 - 14)	Screws Required
50mm	125mm	125mm	4 per panel for each fixing point
75mm	150mm	150mm	4 per panel for each fixing point
100mm	175mm	200mm	4 per panel for each fixing point
125mm	200mm	200mm	4 per panel for each fixing point
150mm	225mm	250mm	4 per panel for each fixing point

- Tek 12 x 20 stitching screws required every 900mm on overlap for bracing
- All Tek 14 & Type 17 to have cyclonic washer

Trim (Ribbed) Profile



General Data

Panel Size (mm)	50	75	100	125	150	175	200	250
TRIM Overall Thickness	78	103	128	153	178	203	228	253
Panel Weight (kg/m ²)	10.58	10.94	11.37	11.80	12.23	12.66	13.09	13.52
R Value 80°C m ² KW	1.61	2.26	2.66	3.25	3.94	-	5.34	-
R Value 20°C m ² KW	1.59	2.22	2.59	3.17	3.75	-	4.95	-
Width (Panel Coverage)	1000mm							
Length	Cut to Length (min. 1.8m)							
Min. Roof Pitch - CORRO	2° (35mm / 1000mm)							
Roof Profile & Materials	Roof Trim 0.42mm BMT AZ150 G550							
Ceiling Profile & Materials	Ceiling Smooth (flat) 0.6mm BMT AZ150 G300							
Core Materials	SL Grade Expanded Polystyrene - Fire Retardant (EPS-FR) 13.5kg m ³							

Aussie Corro



A modern upgrade to the classic corrugated roof, AUSSIE CORRO delivers an all-in-one insulated panel with a sleek design and superior spanning capabilities compared to traditional roofing.


The huge spans create an architectural feel, while the smooth ceiling has no ugly rafters, adding style to your new entertainment and lifestyle area.

Aussie Corro Fixing Guide

Panel Size	Metal Beam (Tek 14)	Timber Beam (Type 17 - 14)	Screws Required
50mm	125mm	125mm	7 per panel for each fixing point
75mm	150mm	150mm	7 per panel for each fixing point
100mm	175mm	200mm	7 per panel for each fixing point
125mm	200mm	200mm	7 per panel for each fixing point
150mm	200mm	250mm	7 per panel for each fixing point

- Tek 12 x 20 stitching screws required every 900mm on overlap for bracing
- All Tek 14 & Type 17 to have cyclonic washer

Corro Profile



General Data

Panel Size (mm)	50	75	100	125	150	175	200	250
CORRO Overall Thickness	66	91	116	141	166	191	216	241
Panel Weight (kg/m ²)	10.85	11.21	11.65	12.08	12.51	12.96	13.40	13.85
R Value 80°C m ² KW	1.61	2.26	2.66	3.25	3.94	-	5.34	-
R Value 20°C m ² KW	1.59	2.22	2.59	3.17	3.75	-	4.95	-
Width (Panel Coverage)	1000mm							
Length	Cut to Length (min. 1.8m)							
Min. Roof Pitch - CORRO	5° (87mm / 1000mm)							
Roof Profile & Materials	Roof Corro 0.42mm BMT AZ150 G550							
Ceiling Profile & Materials	Ceiling Smooth (flat) 0.6mm BMT AZ150 G300							
Core Materials	SL Grade Expanded Polystyrene - Fire Retardant (EPS-FR) 13.5kg m ³							

Aussie Colours

TRIM & CORRO PANEL ROOF



Surfmist® Off White Shale Grey® Gull Grey Deep Ocean® Mountain Blue Cottage Green® Caulfield Green Dune® Birch Classic Cream® Smooth Cream



Ironstone® Iron Grey Paperbark® Merino Basalt® Basal Jasper® Jasmine Pale Eucalypt® Mist Green Monument® Monolith



Wallaby® Wallaroo Night Sky® Ebony Woodland Grey® Slate Manor Red® Heritage Red Windspray® Armour Grey Zincalume® Alu Zinc

TRIM & CORRO PANEL CEILING




Thredbo White® Bright White Surfmist® Off White

MARINE PLUS COLOURS – PANEL ROOF, FLASHINGS, GUTTERS



Surfmist® Off White Windspray® Armour Grey Dune® Birch Woodland Grey® Slate Monument® Monolith

MARINE PLUS COLOURS – PANEL CEILING, BEAMS



Surfmist® Off White

**Colours are a guide only and may be affected by different screens and devices.

Colours should be checked against a colour swatch prior to purchase.



Marine Plus

Protect against premature deterioration of steel with a 5 LAYER finish for coastal areas & locations close to water including pools.

15 year site specific warranty

Flashings/Gutters/Posts



Thredbo White®
Bright White

Surfmist®
Off White

Evening Haze®
Dusk

Deep Ocean®
Mountain Blue

Cottage Green®
Caulfield Green

Dune®
Birch

Classic Cream®
Smooth Cream



Ironstone®
Iron Grey

Paperbark®
Merino

Shale Grey®
Gull Grey

Basalt®
Basal

Jasper®
Jasmine

Pale Eucalypt®
Mist Green

Monument®
Monolith



Wallaby®
Wallaroo

Night Sky®
Ebony

Woodland Grey®
Slate Grey

Manor Red®
Heritage Red

Windspray®
Armour Grey

Zincalume®
Alu Zinc

Beams



Thredbo White®
Bright White

Surfmist®
Off White

Classic Cream®
Smooth Cream

Paperbark®
Merino

Woodland Grey®
Slate Grey

Monument®
Monolith

Night Sky®
Ebony

Beams can also be Powder Coated for an additional charge

****Colours are a guide only and may be affected by different screens and devices.**

Colours should be checked against a colour swatch prior to purchase.

Aussie Wall




AUSSIE WALL is an all-in-one building solution. Insulated Wall Panels have great thermal properties that help keep buildings warm or cool, saving money on energy bills. The 1.2m wide panels also allow for rapid installation and are available in 0.4mm steel sheets or heavy duty premium panels in 0.6mm steel. Ideal for cold rooms, clean rooms, transportable buildings.

General Data

Panel Size (mm)	50	75	100	125	150	175	200	250
Panel Weight (kg/m ²) - 0.6 BMT	10.7	11.1	11.4	11.8	12.1	12.77	12.8	13.5
Width (Panel Coverage)	1200mm							
Length (mm)	Cut to Length (min. 1.8m)							
Top Skin/Bottom Skin	0.4mm BMT / 0.4mm BMT 0.4mm BMT / 0.6mm BMT							
Material	G300 Z275							
Core Materials	SL Grade Expanded Polystyrene - Fire Retardant (EPS-FR) 13.5kg m ³							
Haunch Cuts	Yes							

Wall Panel Profile



Standard Wall Panel Range

Standard Cold Room Wall Panels consist of 0.4mm steel sheets sandwiching an EPS-FR insulation core. Colour is Off White (Surfmist®) on both sides. Thicknesses from 50mm to 200mm.

Premium Wall Panel Range

Premium Cold Room Wall consist of 0.6mm steel sheets sandwiching an EPS-FR insulation core. Comes as Off White (Surfmist®) on both sides OR different colours are available either one one side of the panel of both sides. Thicknesses from 50mm to 200mm.

WALL PANEL COLOURS



Thredbo
White®
Bright
White

Surfmist®
Off White

Classic
Cream®
Smooth
Cream

Shale
Grey® Gull
Grey

Woodland
Grey®
Slate Grey

Pale
Eucalypt®
Mist Green

Night Sky®
Ebony



Basalt®
Basal

Paperbark
® Merino

Monument
® Monolith

****Colours are a guide only and may be affected by different screens and devices.**

Colours should be checked against a colour swatch prior to purchase.

Aussie Single-Skin Roofing

Single-Skin steel roofing is a cost effective solution for your patio, carport, awnings and more. The VJ ceiling allows for an affordable, stylish design which is complimented by the high gloss paint finish.

The interlocking roof system makes for fast installation and has excellent spanning capabilities.

Single-Skin roofing is available in 0.42 and 0.48 steel which can be combined with integrated skylight strips.

Best of all, it is backed by a 15 year, site-specific warranty.



General Data

Sheet Coverage	331mm
Length	Cut to Order (min 500mm)
Roof Material	0.42 / AZ150 G550 or 0.48 / AZ150 G550
Roof Finish	Top: 25% Gloss, Bottom: 80% Gloss
Min. Roof Pitch	2° or 1° (limited lengths)
Weight (kg/m2)	0.42 / 3.674 or 0.48 / 4.145

Single-Skin Colours

(Top & bottom of sheet)



Thredbo
White®
Bright White
***Not available
in 0.42mm**


Surfmist®
Off White

Classic
Cream®
Smooth
Cream

Paperbark®
Merino

Single-Skin Colours Top & Bottom COMBOS

(not available in 0.48mm)



TOP:
Woodland
Grey® Slate
Grey
BOTTOM:
Thredbo
White®
Bright White

TOP:
Woodland
Grey® Slate
Grey
BOTTOM:
Paperbark®
Merino

TOP:
Monument®
Monolith
BOTTOM:
Surfmist®
Off White

****Colours are a guide only and may be affected by different screens and devices.**

Colours should be checked against a colour swatch prior to purchase.

Aussie Accessories

*Beams, Posts, Lights, Flashing, Gutter, Fixings, Misc

Beams



Steel Beams

100mm, 150mm, 200mm Shurelock Beams designed for superior spanning. Also available in 250mm & 300mm. Powder-coated.



End Caps

Caps the end of beam or fixes beam to brick, block, concrete walls. Powder-coated.



Fascia Hanging Bracket

300mm long End Cap to suspend Beam below the fascia. Powder-coated.



Beam to Wall Bracket

Fixes Beam to a brick wall. Sizes 450mm, 900mm, 1800mm. Powder-coated.



Roof Extenda Bracket

For Flyover Roof - protrudes through existing roofline to support Beam. Sizes 300mm, 400mm, 500mm. Zinc.

Brackets



Fascia Upstand Bracket

Alternative to an Extenda Bracket. Bolts to the rafter and comes out from below the gutter. Powder-coated.



Box Gutter Bracket

Typically used in Gable Roof. Bolts to the rafter and protrudes through the fascia, ending in front of the gutter. Powder-coated.



Tunnel Bracket

Similar to Box Gutter Bracket but this one allows the beam to sit lower than the house gutter.



Rafter Bracket

Bolts to rafter behind the fascia to strengthen receiver channel mounting

Posts



Steel Posts

Steel RHS Post sizes: 90x90, 100x100. Kits include post cutout to suit beam and hardware. Powder-coated.

Posts



Aluminium Posts

Aluminium Post sizes 65mm, 90mm, 150mm.
Powder-coated



4-Hole Base Plate

Secures larger posts to concrete pad. Not recommended for Stand Alone Patios or Carports.



2-Hole Base Plate

65mm Internal Cyclonic Post Bracket to suit Aluminium or Steel Posts. Powder-coated.



Internal Steel Post Bracket

Internal Steel RHS Post Bracket. 90mm, 100mm. Galvanised.



Internal Aluminium Post Bracket

Internal Aluminium Post Bracket. 65mm only. Galvanised.

Lights



LED Downlight

Tri Colour: Warm - Natural - Cool.

Lights



Smart Wifi LED Downlight

Connects with iPhone App (Not Android).



LED Downlight Extension Lead

Low voltage plug-in cable. 6.0m



Skylight

Suits RIBBED Panel - Top & Bottom Strip plus Infill Foam: 5.0m | 7.5m | 9.0m

Flashings



Receiver Channel

Attaches panels to wall or fascia. Surfmist Only.



Barge Capping

Caps sides and top edge of panels. NO DRIP EDGE. Available in 18 colours.



Drip Edge Barge Capping

Caps sides and top edge of panels. DRIP EDGE. Available in 18 colours.



Gutter Fascia

A fascia channel to attach the gutter. Available in 18 colours.

Flashings



Z Flashing

Alternative to Gutter Fascia. NO DRIP EDGE.
Available in 18 colours.



Ridge Capping

Finish the ridge line of a Gable roof. Available
in 18 colours.

Gutters



Square Gutter

140mm high front to conceal roof profile.
Slotted for overflow. Available in 18 colours.



Quad Gutter

90mm high front suits any architecture.
Slotted for overflow. Available in 18 colours.



Stop Ends

Left and Right ends to suit both Square &
Quad gutter profiles.



Gutter Brackets

To suit both Square & Quad gutter profiles.



Universal Drop

100mm x 75mm / 90mm Round.

Screws



Roof Panel Screws

Sizes to suit panel thickness. Metal or Timber screws with washer. Painted.



Tek Screws

Includes NEO. Pack of 100. Painted.



Rivets

Pop Rivets & Structural rivets for steel and aluminium. Pack of 100. Painted.



Screw Bolts

Masonry Screw Bolts. Various sizes. Zinc



Bolts

Hex Head Bolts, Cup Head Bolts, Flat Head Bolts. Various sizes. Zinc, Gal.

Miscellaneous



Solar Panel Bracket

250mm Bracket to suit Trim (Ribbed) Panel or Corro Panel.



Infill Strips

To suit Trim (Ribbed) Panel & Corro Panel.
1.0m



Receiver Channel Foam

Adhesive & Non-Adhesive available. 7.6m rolls.



Flextile

5-40mm Black Base & 50-90mm Grey Base.



Touch Up Paint

Spray paint. 250g can



Silicone

Available Clear, White, Cream, Grey.



General Safety and Handling Guide

General Safety

- Always wear personal protective equipment when handling steel products
- Install fall protection, harnesses and perimeter guardrails as required by state law
- Ensure you use the right tools for the job
- Do not walk on roofing or use power tools in wet and windy conditions
- Don't walk on non-trafficable roofing
- Do not walk on a roof overhang

Handling

- When lifting roof panels off a pack, always lift the panels vertically
- Do not slide or drag roof panels off the pack as this will scratch and dent surfaces
- Consider using a crane to lift roof panels into their final fixing position

Installation


- Check engineering and panel installation drawings to ensure the building structure will support the weight of the panels before placing them on the roof
- Turn up panels at the back and turn down on the gutter side
- Peel back plastic film from the ceiling join and the beam end before installing
- Remove metal shavings following cutting or drilling
- Remove metal scraps, uncured sealant or concrete residue
- Treat all cut metal with appropriate rust protection


Delivery and Storage

- Confirm the site is accessible to delivery vehicles
- Select a suitable, level location to unload and store delivered products
- Check if all materials delivered match your order before using them.
- Protect products in the open with a waterproof cover.
- Products can warp if exposed to the sun for long periods
- Powder-coated materials should not be left in plastic packaging for long periods

CUSTOMER COLLECTION

- Customers should observe site signage, safety warnings and requirements.
- Customers should bring appropriate tie-downs and padding
- Unsuitable vehicles will not be loaded.
- Overhang limits apply.
- Customers are responsible for the safe and lawful transport of the goods after they have been loaded.
- Customers should review their obligations on the National Transport Commission website ntc.gov.au or seek advice from the state department of transport and main roads.





\$62/LM inc. gst


"Budget Patio Panels have great joins compared to other panels. They go together well and are easy to assemble."

Ben - Builder

Stocked Lengths: 2.4m, 3.2m, 3.8m, 4.2m, 4.5m, 5.1m, 6.1m

GENERAL DATA

Panel Size	75mm
Overall Thickness	107mm
Panel Weight	10kg/m ²
R Value	R2.16
Width (Panel Coverage)	950mm
Roof Profile & Materials	Roof Trim Deck 0.6mm G300 AZ 150 High Australian Standard Steel
Ceiling Profile & Materials	Ceiling Smooth 0.42mm G300 AZ 150 High Australian Standard Steel
Core Materials	EPS Expanded Polystyrene 16kg/m ³
Colour	Off White both sides
Wind Classification N1	5.8m Span - Overhang 900mm
Wind Classification N3	5.3m Span - Overhang 900mm
Screws - Metal	14x150mm (3 per panel per fixing point)
Screws - Timber	14x175mm (3 per panel per fixing point)





Get in Touch!

(07) 3185 0295

sales@aussiepanels.com.au

8 Andrew Campbell Dr,
Narangba, QLD 4504

Warehouse Hours

Mon - Fri: 8am - 2pm

Sat: 9am - 11am